



CHARACTERISTICS:

- Two vertical 360° and two horizontal 360° laser lines allow for universal use
- Ground-level horizontal 360° laser line for checking the floor for bumps and slopes
- Highly visible laser lines, individually switchable
- Switchable inclination function
- Compact, lightweight, handy
- Switchable pulse function for the use of the optional receiver REC LGD0 in difficult visibility conditions

APPLICATIONS:

- Horizontal leveling
- Inclination manual
- Vertical leveling
- 90° alignment
- Plumbing
- Aligning

PLANO 4D GREEN

Model

PLANO 4D GREEN

Technical details:

Item description	Line and point lasers
Dimensions	150 x 95 x 145 mm
Leveling	Self-leveling
Measuring tolerance	±0.30 mm/m
Self-leveling range	±3°
Application range without handheld receiver (radius)	30 m*
Application range with handheld receiver (radius)	80 m*
Operating temperature	-10°C to +50 °C
Tripod adapter	1/4"
Protection class	IP54
Power supply	2 x 3.6 V (18650) Li-ion battery (2 x 3450 mAh)
Operating time (at 20 °C)	8 hrs (all diodes)
Laser class	2, DIN EN 60825-1 : 2014
Output power	< 1.0 mW
Wavelength	510 - 530 nm